

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
23 December 2004 (23.12.2004)

PCT

(10) International Publication Number
WO 2004/110825 A1

- (51) International Patent Classification⁷: **B60R 21/26**, F42B 3/04
- (21) International Application Number: PCT/US2004/018297
- (22) International Filing Date: 9 June 2004 (09.06.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
10/458,179 11 June 2003 (11.06.2003) US
- (71) Applicant (for all designated States except US): **ZODIAC AUTOMOTIVE US INC.** [US/US]; 1850 West Drake Drive, Tempe, AZ 85283-4303 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **SHILLIDAY, David** [US/US]; 1717 E. Union Hills #2034, Phoenix, AZ 85024 (US). **SCAVEN, Gregory, J.** [US/US]; 2037 E. Hermosa Vista Drive, Mesa, AZ 85213 (US). **FITZGERALD, Kevin** [US/US]; 6604 E. Regina Street, Mesa, AZ 85204 (US).
- (74) Agent: **PRAATT, John, S.**; Kilpatrick Stockton LLP, Suite 2800, 1100 Peachtree Street, Atlanta, GA 30309-4530 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DISTRIBUTED CHARGE INFLATOR SYSTEM



(57) Abstract: An inflatable system includes an inflatable component and an distributed charge inflator disposed in the inflatable component. The distributed charge inflator includes a first charge for generating inflating gas and a housing body connected to the first charge. The housing body includes an initiator and a second charge that has relatively long burn time. Upon receiving a signal from a sensor, the initiator ignites the first charge and the second charge simultaneously. The first charge inflates the inflatable component and the second charge sustains the inflation of the inflatable component.

WO 2004/110825 A1

BEST AVAILABLE COPY

DISTRIBUTED CHARGE INFLATOR SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of U.S. Serial No. 10/458,179 filed on June 11, 2003, which is a continuation-in-part of U.S. Serial No. 10/146,933 filed on May 17, 2002, the contents of which are herein incorporated by reference in its entirety.

BACKGROUND

Field of the Invention

The present invention relates generally to the field of gas-generating devices for inflatable systems, and particularly to those used in inflatable restraint systems.

Background of the Invention

Prior art inflatable systems typically use an initiator (such as an electronic squib) and a booster material (such as boron potassium nitrate) to ignite a surrounding, much larger quantity of gas-generating propellant material (such as sodium azide, potassium nitrate or ammonium nitrate, and binders). The gas-generating propellant serves as the primary means by which sufficient gas is produced to deploy the inflatable system. The initiator, the booster material, and the surrounding gas-generating propellant are typically all confined within a metallic structure or assembly, the whole of which forms the "gas generator" which produces inflating gas for an inflatable component (such as an air bag in a passenger vehicle).

This gas generator assembly typically contains one or more internal chambers or baffles, as well as one or more internal sets of filters, which are designed to: (a) control the burn rate of the propellant and the gas mass flow rate, (b) reduce the temperature of the gases produced by the burning of the gas-generating material, and (c) filter out accelerated particles before the gases pass through vents in the assembly and into the airbag itself.

The gas generator is typically located in a position external to the inflatable component (e.g. an airbag) itself, and is attached to the inflatable component by a conduit through which the generated gases flow into the inflatable component, causing the inflatable component to deploy.

Such prior art systems are disclosed, for example, in U.S. Patent No. 5,738,374 (a pyrotechnic gas generator for an air bag using an annular charge of a mixture of ammonium perchlorate and sodium nitrate, with a silicone binder); U.S. patent No.

5,623,115 (a gas generator including a pyrogen igniter enclosing a unitary grain of ignition material, with a squib located to ignite the unitary grain); U.S. Patent No. 5,483,896 (a housing for a pyrotechnic inflator which serves as a filter for entrapping contaminants and as a cooler by absorbing heat from the generated gas); U.S. Patent No. 5,443,286 (a gas generating cartridge surrounded by filtering and cooling screens); U.S. Patent No. 4,200,615 (a linear igniter and pyrotechnic material extending longitudinally within an elongated enclosure); U.S. Patent No. 4,950,458 (a two-stage gas generator, in which each stage includes a combustion chamber with an igniter); and U.S. Patent No. 4,923,212 (a lightweight pyrotechnic inflator consisting of six component parts, including mechanical parts, a filter, a propellant assembly and an initiator).

Hybrid inflators such as the inflators disclosed in U.S. Patent No. 5,670,738 (a hybrid inflator using compressed gas together with an initiator and a pyrotechnic gas generator), U.S. Patent, No. 5,660,412 (a hybrid inflator consisting of a pressure vessel containing a main charge of pyrotechnic material and a secondary charge of pyrotechnic material, wherein the secondary charge produces products of combustion that ignite the main charge), U.S. Patent No. 5,588,676 (a hybrid inflator with a pyrotechnic gas generator and a gas chamber storing pressurized gas), U.S. Patent No. 5,462,307 (a hybrid air bag inflator with a first chamber containing compressed gas and a second chamber containing an igniter and pyrotechnic material) and U.S. Patent No. 5,131,680 (an inflator assembly which includes pyrotechnic material and a container of gas under pressure) also use gas generating units that are completely separate from and external to the inflatable component (e.g., the air bag) itself.

U.S. Patent No. 6,062,143, which is assigned to the assignee of the present application and is incorporated herein by reference, discloses a distributed charge inflator. The distributed charge inflator generally includes a distributed gas-generating material, that may have a faster burning center core ignition material surrounded by supplemental propellant, or uses a homogenous mixture of ignition material and propellant, and also includes an initiator (e.g., an electronic squib) used to ignite the gas generating material upon a signal from an initiating device. The fast burning gas generating material or "distributed charge" is designed to be installed within and distributed along the interior of the undeployed inflatable component itself. It is not necessary to contain the distributed charge inflator (DCI) within any type of exterior housing or assembly. The distributed charge inflator is simpler and less expensive to manufacture than the prior art systems listed above, because it does not require the complicated series of chambers, baffles, or

filters. Also, because distributed charge inflator is distributed, rather than confined to a small enclosed container as in the prior art systems listed above, it generates gases and releases the generated gases with far less explosive force than in the prior art systems. The internal distributed charge inflator system virtually eliminates the uneven inflations, pressure waves, and inertial effects of gases injected into the inflatable components from externally located gas generators. Moreover, the distributed charge inflator equipped inflatable restraints deploy less aggressively than existing systems because the energy of the expanding gases is essentially distributed uniformly throughout the inflatable structure during deployment.

Further, because the distributed charge inflator is distributed internally within the inflatable component, there is no necessity to reinforce the inflatable fabric or bladder material against pressure, heat and high velocity particulates at the point at which gases would have been forcefully injected into the inflatable component from the gas generator external to the inflatable component. Furthermore, there is no need for a reinforced fill tube, or other means for providing a secure conduit from the gas generator to the inflatable component.

An additional advantage is that it can be readily scaled to the particular application. Almost every different vehicle platform or different application requires a different volume of the inflating gas, or a different rate of inflation.

The distributed charge inflator is not limited to simply propagating the rapid ignition of other materials, the burning of which then produces the quantities of gas necessary to inflate a given structure. The distributed charge inflator system is a complete, autonomously-operating inflation system.

Example of inflatable components which the distributed charge inflator can be used to inflate are described in U.S. Patent No. 5,282,648 (body and head restraints); U.S. Patent No. 5,322,322 (side impact head strike protection); U.S. Patent No. 5,480,181 (side impact head strike protection); and U.S. Patent No. 5,464,246 (tubular cushions), which are incorporated herein by reference, as well as automotive air bags and other inflatable products.

SUMMARY OF THE INVENTION

The present invention is an improved inflator system that can be used in conjunction with a wide variety of inflatable systems such as inflatable restraint systems, inflatable flotation systems, or passive inflatable safety systems.

An inflatable system of the present invention includes an inflatable component and a distributed charge inflator disposed in the inflatable component. The distributed charge inflator includes a housing body and a distributed charge connected to the housing body. Upon receiving a signal from a sensor, an initiator in the housing body ignites the distributed charge, thus inflating the inflatable component.

The housing body may also include a sustainer having a longer burn time than the distributed charge. The initiator ignites the distributed charge and the sustainer simultaneously upon receiving the signal from the sensor. The distributed charge combusts over a first time interval to inflate the inflatable component and the sustainer combusts over a second time interval to maintain the inflation of the inflatable component. Optionally, the housing body may include a booster to help the ignition of the distributed charge. The booster may be loosely placed within the housing body. Alternatively, the booster may be compressed in a container that is placed around the initiator in the housing body.

The distributed charge inflator of the present invention may be used in a side impact protection system. In one embodiment, the distributed charge inflator includes a housing body and more than one distributed charge having different deployment characteristics. The distributed charge inflator is disposed in an inflatable component of the side impact protection system. Each of the distributed charges is disposed in different sections (e.g., chambers) of the inflatable component. The distributed charges, having different deployment characteristics, disposed in the different sections of the inflatable component may cause the different sections of the inflatable component to be inflated with different deployment characteristics, such as different timing, different pressures and/or different burn rates. The distributed charges may assume any shape. The distributed charges do not need to be uniformly (or evenly) distributed within the sections of the inflatable component.

The distributed charge inflator of the present invention may also be used in a front impact protection system. The distributed charge inflator including a distributed charge and a housing body is disposed in an inflatable component of the front impact protection system. The distributed charge may assume any shape. The distributed charge does not need to be uniformly (or evenly) distributed within the inflatable component.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic diagram of an inflatable system according to a preferred embodiment of the present invention.

Figure 2 is a schematic diagram of an exemplary inflatable system according to a preferred embodiment of the present invention.

Figure 2a is a cross-sectional view of the exemplary inflatable system in Figure 2.

Figure 3 is a cross-sectional view of an exemplary distributed charge inflator according to a preferred embodiment of the present invention.

Figures 4, 5 and 6 are schematic diagrams of exemplary implementations of the present invention.

Figure 7 is a schematic diagram of an alternate inflatable system of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

Figure 1 shows an inflatable system according to a preferred embodiment of the present invention.

Inflatable system 100 includes an inflatable component 101 and a distributed charge inflator 110 disposed in inflatable component 101. Distributed charge inflator 110 includes a housing body 102 and a distributed charge 104 connected to housing body 102. Distributed charge 104 may be a solid monolithic block of pyrotechnic materials formed into the desired configuration using binders. The pyrotechnic material (with or without binders) may be enclosed by an exterior sheath, layer or coating for environmental protection. Alternatively, the distributed charge may include a core of ignition material and a sheath. Optionally, the distributed charge may also include a gas generating layer or coating. Housing body 102 includes an initiator for igniting the distributed charge. Housing body 102 may also include a sustainer that exhibits relatively long burn time. Housing body 102 may be any type of inflator. The housing body may be a compressed gas inflator or a hybrid inflator.

Inflatable system 100 receives an electric signal from an activator along a wire 103, when a crash sensor or other activator determines that the inflatable component must be deployed. Upon receiving the electrical signal, the initiator in the housing body ignites

distributed charge 104, generates inflating gas, thus deploying inflatable component 101. Simultaneously, the initiator may also ignite the sustainer in the housing body, thus sustaining the inflation of the inflatable component.

Figure 2 shows an exemplary inflatable system according a preferred embodiment of the present invention.

Inflatable system 200 includes an inflatable component 201 and a distributed charge inflator 210 disposed in inflatable component 201. Distributed charge inflator 210 includes a housing body 202 and a distributed charge 204 connected to housing body 202. Figure 2A shows across-sectional view of inflatable system 200. As shown, housing body 202 includes an initiator 230 and a sustainer 205. Sustainer 205 is held and supported by a retaining ring 220 and a spring 222 in housing body 202. Spring 222 accommodates for different loads of sustainer 205 to suit the specific application. Other elastic materials or mechanisms can be used as alternatives to spring 222. Housing body 202 also includes a nozzle screen 232 and a ferrule 234. Nozzle screen 232 retains sustainer 205 in housing body 202. Ferrule 234 joins housing body 202 to distributed charge 204 by mechanically holding the distributed charge. Ferrule 234 also controls the output of the housing body.

Initiator 230 ignites both of sustainer 205 and distributed charge 204. Combustion of distributed charge 204 generates a high volume of gas which inflates inflatable component 201 from stowed to deployed conditions. The distributed charge typically combusts over a relatively short time interval (typically between 1 and 20 ms, preferably 5 ms). To maintain inflation of the inflatable component, the sustainer is provided to combust over a relatively longer interval (typically between 50 to 500 ms, preferably 200 ms). The gas generated from combustion of the sustainer can be vented from the housing body through the ferrule.

Optionally, housing body 202 may include a booster (not shown) to help the ignition of the distributed charge. The booster may be loosely placed within the housing body. Alternatively, the booster may be compressed in a container and placed in the housing body. Figure 3 shows an exemplary embodiment of the distributed charge inflator including the booster compressed in a container. As shown, a housing body 302 of distributed charge inflator 310 includes an initiator 320 and a booster 333 compressed in a container 330. Container 330 may be placed around initiator 320, thus forming a "micro gas generator." The micro gas generator eliminates the need for a booster assembly packet that is used with the booster loosely placed within the housing body, thus simplifying assembly of the housing body. Further, since the booster is compressed, the

booster combusts more efficiently than the loosely placed booster. Boron potassium nitrate (BKN03), for example, may be used as the booster.

The length of the time intervals over which the distributed charge and the sustainer are combusted can be selected for the particular application. For example, the inflatable component for a side impact protection system for a sports utility vehicle needs to become fully inflated within 15 ms, and needs to remain inflated for at least 2.5 seconds, preferably as long as 7 seconds or more so that it can protect its occupants in a rollover. Preferably, the inflatable component for front impact protection system should become fully inflated within 30 ms and should remain inflated for 100 ms.

The distributed charge in the distributed charge inflator may be manufactured in various sizes and configurations, depending upon the inflation requirements of the system for which it is intended. These may range from a foil or thin film, or linear or tubular shaped charges to broad flat sheets of distributed charge material which may be cut, trimmed, or otherwise fitted. For example, distributed charge 104 in Figure 1 and distributed charge 204 in Figure 2 are configured as linear charges.

Further, the distributed charge inflator of the present invention can be designed so that, depending on deployment characteristics of the distributed charges or the pattern of distribution of the distributed charges within a given inflatable system, different sections of the inflatable component can be inflated with different deployment characteristics, such as different timing, different pressures and/or different burn rates.

Figures 4, 5 and 6 show examples of implementations of the present invention.

Figure 4 shows an exemplary implementation of the distributed charge inflator of the present invention in a side impact protection system. As shown, the distributed charge inflator includes a housing body and more than one linear charge (i.e., a distributed charge in linear configuration) connected to the housing body. The distributed charge inflator includes housing body 402 and linear charges 403 and 404 connected to housing body 402. Housing body 402 includes an initiator for igniting the linear charges. Housing body 402 may also include a sustainer. The distributed charge inflator is disposed in inflatable component 401 of the side impact protection system. The inflatable component of the side impact protect system includes multiple sections (or chambers). For example, inflatable component 401 includes sections 410 and 412. Each of the linear charges is disposed in each of the multiple sections of the inflatable component. Linear charge 403 is disposed in section 410 and linear charge 404 is disposed in section 412 of inflatable component 401. The linear charges may assume any shape. For example, the linear

charges may be coiled, as shown in Figure 4, or straight or knotted. Figure 5 illustrates linear charge 403 with different shape. Linear charges 403 and 404 are configured to have different deployment characteristics so that the sections of the inflatable component can be inflated with different timing, different pressures and/or different burn rates, depending upon the inflation requirements of the system for which it is intended. The length of the linear charges can be selected so as to control the deployment time and the pressure of different sections of the inflatable component. The linear charges may be formed of different materials or composition having different burn rates. The linear charges may also be in different shapes.

The initiator in housing body 402 ignites both of linear charges 403 and 404 upon receiving a signal from an activator. Ignition of linear charge 403 and 404 causes inflation of inflatable component 401 with sections 410 and 412 inflating with different timing and/or different pressures. By providing the linear charges having different deployment characteristics in the different sections of the inflatable component, the inflatable component can be inflated with the different sections of the inflatable component inflating with different deployment characteristics, such as different timing, different pressures and/or different burn rates depending upon the inflation requirements of the system for which it is intended. The sections of the inflatable component that inflates fast, for example, can provide protection for rapid crash event, such as a primary impact, and the sections of the inflatable component that inflates slowly and has a long burn time can provide protection for slower developing crash events, such as a rollover.

The linear charge does not need to be uniformly (or evenly) distributed within the section of the inflatable component. Even without the linear charge evenly distributed in the inflatable component, the distributed charge inflator of the present invention provides advantages over the prior art systems. The distributed charge inflator of the present invention is still simpler and less expensive to manufacture than the prior art systems because it does not require the complicated series of chambers. Also, because the linear charge is not confined to a small enclosed container, it generates gases and releases the generated gases with far less explosive force than in the prior art systems. Further, when the linear charge is disposed within the inflatable component, there is no necessity to reinforce the inflatable fabric. Furthermore, there is no need for a reinforced fill tube, or other means for providing a secure conduit from the gas generator to the inflatable component.

Figure 6 shows an exemplary implementation of the distributed charge inflator of the present invention in a front impact protection system. The distributed charge inflator includes a housing body 602 and a linear charge 603 connected to the housing body. The distributed charge inflator is disposed in an inflatable component 601. Linear charge 603 may assume any shape. In Figure 6, for example, linear charge 602 is coiled. The linear charge does not need to be evenly distributed within the inflatable component. The front impact protection system may be mounted in an instrument panel 604 of an automobile.

Illustrated in Figure 7 is an alternate inflatable system 700 substantially similar to inflatable system 100 of Figure 1. Included in system 700 are an inflatable component 701 and a distributed charge inflator 710 disposed therein. Like inflator 110 of Figure 1, distributed charge inflator 710 may include a housing body 702 and a distributed charge 704 connected thereto. However, initiator 730 need not be positioned at an end of housing body 702 opposite distributed charge 704, but rather may be positioned anywhere appropriate along or within housing body 702. Indeed, in some embodiments of the invention (an exemplary one of which is shown in Figure 7), initiator 730 may be near or adjacent either or both of distributed charge 704 and any container present in the housing so as to reduce further the interval between when an initiating signal is received by initiator 730 via wire 703 and charge 704 and any sustainer or booster is ignited or otherwise initiated. Further, as should be readily apparent to those skilled in the relevant field, either or both of any sustainer or booster present in the invention may comprise compressed gas housed in a container, with the gas having an onset rate differing from (and, at least for any sustainer, typically slower than) the burn or onset rate of charge 704.

The foregoing disclosure of the preferred embodiments of the present invention has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many variations and modifications of the embodiments described herein will be apparent to one of ordinary skill in the art in light of the above disclosure. The scope of the invention is to be defined only by the claims appended hereto, and by their equivalents.

Further, in describing representative embodiments of the present invention, the specification may have presented the method and/or process of the present invention as a particular sequence of steps. However, to the extent that the method or process does not rely on the particular order of steps set forth herein, the method or process should not be limited to the particular sequence of steps described. As one of ordinary skill in the art

would appreciate, other sequences of steps may be possible. Therefore, the particular order of the steps set forth in the specification should not be construed as limitations on the claims. In addition, the claims directed to the method and/or process of the present invention should not be limited to the performance of their steps in the order written, and one skilled in the art can readily appreciate that the sequences may be varied and still remain within the spirit and scope of the present invention.

WHAT IS CLAIMED IS:

1. An inflatable system comprising:
 - an inflatable component;
 - a first charge for generating inflating gas; and
 - a housing body including an initiator and connected to the first charge, wherein the first charge and the housing body are disposed in the inflatable component, and the initiator ignites the first charge and generates inflating gas which inflates the inflatable component.
2. The inflatable system of claim 1, wherein the housing body further includes a second charge having burn time longer than burn time of the first charge.
3. The inflatable system of claim 2, wherein the initiator ignites the first charge and the second charge simultaneously.
4. The inflatable system of claim 2, wherein the first charge inflates the inflatable component and the second charge maintains the inflation of the inflatable component.
5. The inflatable system of claim 2, wherein the system further includes a third charge to boost the ignition of the first charge.
6. The inflatable system of claim 5, wherein the third charge is compressed in a container.
7. The inflatable system of claim 6, wherein the container is placed around the initiator in the housing body.
8. The inflatable system of claim 1, wherein the first charge is a solid monolithic block of pyrotechnic materials in linear configuration.
9. The inflatable system of claim 1, wherein the system includes a plurality of the first charges connected to the housing body and the inflatable component includes a plurality of sections.

10. The inflatable system of claim 9, wherein the initiator ignites the plurality of the first charges.

11. The inflatable system of claim 9, wherein each of the plurality of the first charges is disposed in each of the plurality of sections of the inflatable component.

12. The inflatable system of claim 11, wherein the plurality of the first charges has different deployment characteristics and the ignition of the plurality of the first charge causes inflation of the plurality of sections of the inflatable component with different deployment characteristics.

13. The inflatable system of claim 12, wherein the different deployment characteristics include different timing, different pressures or different burn rates.

14. The inflatable system of claim 12, wherein the deployment characteristics are determined by a shape, a length or a composition of the first charge.

15. An inflatable system comprising:

an inflatable component including a plurality of chambers, wherein the plurality of chambers include a first chamber and a second chamber;

a plurality of charges for generating inflating gas, wherein the plurality of charges include a first charge and a second charge, the first charge is disposed in the first chamber and the second charge is disposed in the second chamber; and

a housing body including an initiator and connected to the plurality of charges, wherein the initiator ignites the plurality of charges and generates inflating gas which inflates the inflatable component such that the first chamber and the second chamber of the inflatable component are inflated with different deployment characteristics.

16. The inflatable system of claim 15, wherein the first charge and the second charge have different deployment characteristics.

17. The inflatable system of claim 16, wherein the deployment characteristics are determined by a shape, a length or a composition of each of the first charge and the second charge.
18. The inflatable system of claim 15, wherein the different deployment characteristics include different timing, different pressures or different burn rates.
19. The inflatable system of claim 15, wherein the first chamber of the inflatable component provides protection for a rapid crash event and the second chamber of the inflatable component provides protection for slower developing crash events.
20. The inflatable system of claim 15, wherein the first charge and the second charge have a linear configuration that can assume any shape.
21. The inflatable system of claim 15, wherein the housing body further includes a third charge for maintaining the inflation of the inflatable component.
22. The inflatable system of claim 21, wherein the initiator ignites the first charge, the second charge and the third charge simultaneously.
23. The inflatable system of claim 15, wherein the housing body further includes a fourth charge to boost the ignition of the plurality of charges.
24. The inflatable system of claim 23, wherein the fourth charge is compressed in a container and the container is placed around the initiator.
25. The inflatable system of claim 1, wherein the housing body further includes a second charge having a gas onset rate slower than that of the first charge.
26. The inflatable system of claim 2, wherein the initiator initiates the first and second charges simultaneously.
27. The inflatable system of claim 2, wherein the second charge is compressed in a container.

28. The inflatable system of claim 6, wherein the container is placed adjacent to the initiator in the housing body.

1/5




Figure 1




Figure 2

2/5




Figure 2A




Figure 3




Figure 4




Figure 5

4/5





Figure 6



INTERNATIONAL SEARCH REPORT

National Application No

US2004/018297

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B60R21/26 F42B3/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B60R F42B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with Indication, where appropriate, of the relevant passages	Relevant to claim No.
X Y	WO 01/34516 A (GREGG GARY S ; HOLLAND GARY F (US); ITALIANE JOHN R (US); NGUYEN ANDRE) 17 May 2001 (2001-05-17) page 5 - page 10; figures 1-3	1-5, 25, 26 8-14, 19, 21, 22
X Y	US 6 062 143 A (RICHARDS MARVIN K ET AL) 16 May 2000 (2000-05-16)	1, 15-18, 20 8-14, 19, 21, 22
A	DE 200 13 405 U (LELL PETER) 15 February 2001 (2001-02-15) the whole document	1, 15

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

11 October 2004

Date of mailing of the international search report

20/10/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Ziegler, H-J

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

.../US2004/018297

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0134516	A	17-05-2001	AU 1758201 A JP 2003525106 T WO 0134516 A2	06-06-2001 26-08-2003 17-05-2001
US 6062143	A	16-05-2000	AU 9774198 A BR 9806165 A CA 2270914 A1 EP 0941180 A1 JP 2001519746 T WO 9912776 A1	29-03-1999 19-10-1999 18-03-1999 15-09-1999 23-10-2001 18-03-1999
DE 20013405	U	15-02-2001	DE 20013405 U1 DE 10138246 A1	15-02-2001 04-07-2002